

ORBIT 3

SPECIFICATIONS

MOUNTING		CEILING / WALL	
POWER	[W]	7,5	
LAMP		built-in LED	
LUMINOUS FLUX*	[lm]	660	
LIGHT COLOUR	[K]	2700	
CRI		>90	
BEAM ANGLE	[°]	-	
AVERAGE LIFETIME	[h]	L80/B50.000	
LUMINOUS EFFICACY	[lm/W]	88	
POWER SUPPLY	[V] [A]	220-240V AC 50/60 Hz	
LED-DRIVER		INCLUDED	
DIMMING		NO	
THROUGH-WIRING		NO	
MATERIAL		ALUMINUM	
INGRESS PROTECTION		IP20	
PROTECTION CLASS		I	
NET WEIGHT	[kg]	1,23	
GROSS WEIGHT	[kg]	1,25	
COLOUR (HOUSING)		BLACK ~RAL9005	n/a



LIGHT DISTRIBUTION

n/a

*Luminous flux values are nominal LED data at a operating temperature of 25° C


OPTIONS / OPTIONAL ACCESSORIES

Colours




black

MOUNTING DIMENSIONS



FIXTURE DIMENSIONS



DLS LIGHTING

www.dslighting.com

***DLS**
LIGHTING